

BEST AVAILABLE COPY

Serial No. 10/666,825

Docket No. NG(ST)7616

RECEIVED
CENTRAL FAX CENTER

FEB 15 2007

LISTING OF THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) For use in an ultra wideband (UWB) communication system, a method for communicating binary data, having logical "0" and "1" value types, as a sequence of UWB pulses, the method comprising:

encoding binary data of one value type as positive UWB pulses and binary data of the other value type as negative UWB pulses; and

detecting the presence of positive and negative UWB pulses using a zero-amplitude level sensing threshold, thereby increasing immunity to noise.

2. (Currently Amended) A method as defined in claim 1, wherein:

each of the UWB pulse pulses includes a carrier signal; and

each of the negative UWB pulse pulses has its carrier phase inverted.

3. (Original) A method as defined in claim 2, wherein the detecting step comprises:

sensing whether the carrier phase is inverted or not;

rectifying and filtering the UWB carrier signal pulse to provide a unidirectional signal;

and

adjusting the polarity of the unidirectional signal based on whether the sensed carrier phase is inverted or not.

4. (Original) A method as defined in claim 3, wherein:

the UWB pulses are generated in predetermined time slots; and

the method further comprises assigning portions of each time slot to respective communication channels, whereby data signals pertaining to multiple communication channels are transmitted in a single time slot.

BEST AVAILABLE COPY

Serial No. 10/666,825

Docket No. NG(ST)7616

5. (Original) A method as defined in claim 4, wherein:
- each UWB pulse time slot has two half time slots;
 - data signals pertaining to first and second communication channels are encoded in the first and second halves, respectively, of each UWB pulse time slot.